

ARAMID ELYAF KUMAŞLAR

| URUN KODU | threadxcm | | elyaf | | kalınlık | ağırlık | | | dokuma | |
|-------------------------|---------------|------|--------|------|--------------------|-------------|------|--------|----------|-----------------|
| | çözüğü | atkı | çözüğü | atkı | | çözüğü | atkı | toplam | | |
| | UNI EN 1049-2 | | TEX | | (mm)+-15% | (gr/m2)+-4% | | | UNI 8099 | |
| | | | | | UNI EN ISO 5084 | UNI 5114-82 | | | | |
| KEVLAR®49-DuPont | | | | | | | | | | |
| STYLE | 120 | 13 | 13 | 215 | 215 | 0,08 | 30 | 30 | 60 | plain |
| STYLE | 220 | 9,5 | 9,5 | 420 | 420 | 0,12 | 40 | 40 | 80 | plain |
| STYLE | 115 | 13,3 | 13,3 | 420 | 420 | 0,15 | 58 | 58 | 115 | plain |
| STYLE | 181 | 20 | 20 | 420 | 420 | 0,23 | 84 | 84 | 168 | 8 H satin |
| STYLE | 281 | 6,7 | 6,7 | 1270 | 1270 | 0,25 | 86,5 | 86,5 | 173 | plain |
| STYLE | 285 | 6,7 | 6,7 | 1270 | 1270 | 0,25 | 86,5 | 86,5 | 173 | crowsfoot satin |
| STYLE | 282 | 6,7 | 6,7 | 1270 | 1270 | 0,25 | 86,5 | 86,5 | 173 | twil 2/2 |
| STYLE | 143 | 39 | 8 | 420 | 220 | 0,30 | 163 | 163 | 196 | crowsfoot satin |
| STYLE | 243 | 15 | 7 | 1270 | 420 | 0,30 | 190 | 30 | 220 | crowsfoot satin |
| STYLE | 328 | 6,7 | 6,7 | 1580 | 1580 | 0,33 | 111 | 111 | 223 | plain |
| STYLE | 335 | 6,7 | 6,7 | 1580 | 1580 | 0,33 | 111 | 111 | 223 | crowsfoot satin |
| STYLE | 279 | 4,4 | 4,3 | 3160 | 3160 | 0,32 | 139 | 136 | 275 | twil 2/2 |
| STYLE | 900 | 6,7 | 6,7 | 2400 | 2400 | 0,40 | 163 | 163 | 326 | 5 H satin |
| STYLE | 1050 | 11 | 11 | 1580 | 1580 | 0,46 | 178 | 178 | 356 | basket 4/4 |
| STYLE | 380 | 15,5 | 2 | 2400 | 215 | 0,40 | 375 | 5 | 380 | oxford 2/1 |
| STYLE | 1350 | 9,3 | 9,3 | 2400 | 2400 | 0,68 | 225 | 225 | 450 | basket 4/4 |
| STYLE | 1033 | 7,85 | 7,85 | 3160 | 3160 | 0,62 | 260 | 225 | 520 | basket 4/4 |

